



PCE Americas Inc.
 711 Commerce Way
 Suite 8
 Jupiter
 FL-33458
 USA
 From outside US: +1
 Tel: (561) 320-9162
 Fax: (561) 320-9176
 info@pce-americas.com

PCE Instruments UK Ltd.
 Units 12/13
 Southpoint Business Park
 Ensign way
 Hampshire / Southampton
 United Kingdom, SO31 4RF
 From outside UK: +44
 Tel: (0) 2380 98703 0
 Fax: (0) 2380 98703 9
 info@pce-instruments.com

www.pce-instruments.com/english
www.pce-instruments.com

Technical Air Sampler PCE-PCO 1

PCE-PCO 1 Particle Counter

Measures 6 particle sizes / Features built-in camera, air temperature and relative humidity sensors

PCE-PCO 1 is a laser particle counter for measuring the concentration of particles in the air. The PCE-PCO 1 particle counter:

- Measures 6 sizes of particles: 0.3 µm, 0.5 µm, 1.0 µm, 2.5 µm, 5.0 µm, 10 µm
- Offers a robust, 80 MB internal memory
- Features a large, full-color LCD display with backlight
- Includes a built-in camera for image and video recording
- Contains sensors for measuring air temperature and relative humidity

The PCE-PCO 1 particle counter is ideal for monitoring clean rooms, indoor air quality, exposure to exhaust, smoke, mold, respirable crystalline silica dust (RCS) and other harmful air pollutants, and levels of airborne combustible dust such as agricultural dust, carbonaceous dust, chemical dust, metal dust, plastic dust and wood dust.

A variety of materials are explosible in dust form. Some examples include: food (e.g., candy, sugar, spice, starch, flour and feed), grain, tobacco, plastics, wood, paper, pulp, rubber, pesticides, pharmaceuticals, dyes, coal and metals (e.g., aluminum, chromium, iron, magnesium and zinc). These materials are used in agriculture, chemical manufacturing, pharmaceutical production, furniture, textiles, fossil fuel power generation, recycling operations, metal working and processing (including additive manufacturing and 3D printing) and many other industries and processes.

In addition to being a combustion hazard, certain kinds of dust can be a health hazard. Exposure (such as skin contact, eye contact and inhalation) can be linked to sneezing, a stuffy or runny nose, itchy or red eyes, headaches, fatigue, fever, cough, shortness of breath, dermatitis, asthma, bronchitis, pneumonia (e.g., Legionnaires' disease and hypersensitivity pneumonitis), silicosis and asbestosis, as well as mesothelioma, lung and other cancers.

General technical specifications

| | |
|--------------------------|------------------------------------------------------------------|
| Environmental conditions | 0 ... 50 °C, 10 ... 90 % RH (non-condensing) |
| LCD Display | 2.8 " / 320 x 240 pixels, back-lit, color |
| Rechargeable battery | Operating time ~ 4 hours |
| Dimensions | 240 x 75 x 55 mm |
| Weight | 420 g |
| Memory | Internal: 80 MB External: Micro SD card up to 8 GB (optional) |

Particle counting specifications

| | |
|--------------------------------------|----------------------------------------------------------------------------------|
| Measurable particle sizes (channels) | 0.3 µm / 0.5 µm / 1.0 µm / 2.5 µm / 5.0 µm / 10 µm |
| Flow rate | 0.1 cfm (2.83 L/min) |
| Coincidence error | <5% at 2,000,000 particles per cubic foot |
| Counting efficiency | 50 % at particle size 0.3 µm 100 % at particle size > 0.45 µm (per ISO 21501) |
| Data storage | 5000 records |
| Counting modes | Cumulative, differential, concentration |

Air temperature and relative humidity measuring specifications

| | |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Air temperature measuring range | 0 ... +50°C |
| Air temperature precision | ±0.5 °C with +10 ... +40 °C Otherwise ± 1 °C |
| Dew point temperature measuring range | 0 ... +50°C |
| Dew point temperature precision | ±0.5 °C with +10 ... +40 °C Otherwise ± 1 °C |
| Relative humidity measuring range | 0 ... 100 % RH |
| Relative humidity precision | ±3 % RH with 40 ... 60 % ±3.5 % RH with 20 ... 40 % and 60 ... 80 % ±5 % RH with 0 ... 20 % and 80 ... 100 % |

Delivery contents

- 1 x PCE-PCO 1 particle counter
- 1 x zero filter
- 1 x rechargeable battery
- 1 x charger
- 1 x USB cable
- 1 x user manual
- 1 x CD-ROM (software)
- 1 x tripod
- 1 x hard case