



pH Meter PCE-CP 21



Multi-parameter pH meter with Bluetooth interface / PC software / Cloud service / Cross-system synchronization of measured values / Up to 13 selectable parameters / For measuring e.g. pH, alkalinity, chlorine, cyanuric acid / Storage of measured values

The multi-parameter pH meter is a mobile measuring device for liquid analysis. This enables the most varied of measurements to be carried out with the multi-parameter photometer. With this multi-parameter photometer, for example, it is possible to determine alkalinity, chlorine, cyanuric acid or the pH value. In order to carry out a measurement with the multi-parameter photometer, a water sample of 10 ml must be placed in a cuvette. The built-in LED in the multi-parameter photometer generates a test light in the wavelength ranges of 503 nm, 570 nm and 620 nm. A photodiode now recognizes the value to be measured based on the light transmission of the sample.

Each measurement is automatically saved by the multi-parameter pH meter. The stored measured values can then be read out, for example, via a mobile device via the Bluetooth interface built into the multi-parameter photometer. A free app is available to analyze the measured values from the multi-parameter photometer. It is also possible to establish a Bluetooth connection between the multi-parameter photometer and a computer. Free software is also available for this, with which the measurement data can be analyzed. As another special feature of the multi-parameter photometer, the measurement data can be uploaded to a cloud using both variants and accessed from anywhere. This service for the multi-parameter photometer is also free of charge.

- ▶ Up to 13 selectable parameters
- ▶ Bluetooth connection with app
- ▶ Exchangeable and lockable cuvette
- ▶ 503 nm / 570 nm / 620 nm LED
- ▶ Automatic shutdown when inactive
- ▶ Many different menu languages
- ▶ Light detector: photodiode
- ▶ Cuvette: 36 x ø 21 mm / 3.6 x ø 2.1 cm (10 ml)

Subject to change

Specifications

Chlorine

| | |
|-----------------|--------------------|
| Measuring range | 0.00 ... 2.00 mg/l |
| | 2.00 ... 3.00 mg/l |
| | 3.00 ... 4.00 mg/l |
| | 4.00 ... 8.00 mg/l |

| | |
|----------|-----------|
| Accuracy | 0.10 mg/l |
| | 0.23 mg/l |
| | 0.75 mg/l |
| | 1.00 mg/l |

| | |
|------------|-----------|
| Resolution | 0.01 mg/l |
|------------|-----------|

pH

| | |
|-----------------|------------------|
| Measuring range | 6.50 ... 8.40 pH |
| Accuracy | 0.11 pH |
| Resolution | 0.01 pH |

Iron

| | |
|-----------------|--------------------|
| Measuring range | 0.00 ... 0.20 mg/l |
| | 0.20 ... 0.60 mg/l |
| | 0.60 ... 1.00 mg/l |

| | |
|----------|-----------|
| Accuracy | 0.02 mg/l |
| | 0.04 mg/l |
| | 0.08 mg/l |

| | |
|------------|-----------|
| Resolution | 0.01 mg/l |
|------------|-----------|

Cyanuric acid

| | |
|-----------------|------------------|
| Measuring range | 0 ... 15 mg/l |
| | 15 ... 50 mg/l |
| | 50 ... 120 mg/l |
| | 120 ... 160 mg/l |

| | |
|----------|---------|
| Accuracy | 1 mg/l |
| | 5 mg/l |
| | 13 mg/l |
| | 19 mg/l |

| | |
|------------|--------|
| Resolution | 1 mg/l |
|------------|--------|

Bromine

| | |
|-----------------|--------------------|
| Measuring range | 0.0 ... 2.5 mg/l |
| | 2.5 ... 6.5 mg/l |
| | 6.5 ... 11.0 mg/l |
| | 11.0 ... 13.5 mg/l |

More information

Manual



More product info



Similar products



Subject to change



Accuracy 0.2 mg/l
0.6 mg/l
1.7 mg/l
2.3 mg/l

Resolution 0.1 mg/l

Iodine

Measuring range 0.0 ... 5.0 mg/l
5.1 ... 10.0 mg/l
10.1 ... 15.0 mg/l
15.1 ... 21.4 mg/l

Accuracy 0.5 mg/l
0.8 mg/l
2.7 mg/l
3.6 mg/l

Resolution 0.1 mg/l

Further specification

Units mg/l, ppm
Calibration Zero point calibration
Light source 503 nm / 570 nm / 620 nm LED
Light detector Photodiode
Power supply 4 x 1.5V AA batteries
Dimensions of the cuvette 36 x ø 21 mm / 3.6 x ø 2.1 cm (10 ml)
Menu languages English, German, French, Spanish and Italian
Storage Automatic storage of measured values and readout
Storage space 256 values
Interface Bluetooth connection with app and PC software
Automatic shutdown After 300 seconds of inactivity
Operating conditions 5... 45 °C, 20 ... 90% RH non-condensing
Storage conditions 5... 45 °C, 20 ... 90% RH non-condensing
Dimensions 165 x 95 x 50 mm / 6.5 x 3.7 x 2 in
Weight 230 g / 8.1 oz

Subject to change

