

# BATTERY TESTER

PCE-IRM 10



- » **test frequency: 1 kHz**
- » **measurement range selection: automatic, manual**
- » **upper and lower limit values adjustable**
- » **pass/fail test function**
- » **automatic power-off**
- » **measurement function: hold**
- » **2.4-inch colour display**
- » **internal memory: 100 KB**
- » **CSV export via USB-C**

The battery tester is a compact and easy-to-use device for testing the battery quality of various battery types such as lithium, alkaline and lead-acid batteries. The battery tester can automatically test the internal resistance and voltage simultaneously, with the measurement results clearly shown on the 2.4-inch colour display. The voltage and resistance ranges can also be set manually.

An important function of the tester is the pass/fail test function, which enables a quick assessment of batteries based on predefined limit values. The user can define upper (UL) and lower (LL) limit values for voltage and resistance. A green light indicates that the battery fulfils the criteria, a red light indicates that it does not fulfil the criteria. Up to 8 limit values can be saved to make the test procedure faster and more efficient.

The test results are automatically saved to the internal memory and can be exported as a CSV file via the USB-C port. The port is also used to charge the device. For reliable measurements, the battery tester uses a 4-way connection with secure fastening by means of a screw ring. In addition, the test results can be provided with date and time, which can be set via a simple menu. The battery tester offers a practical solution for the accurate assessment of batteries and is suitable for applications in the automotive industry as well as for home users.

## Specification

### Direct voltage DC

Measurement range up to 0 ... 100 V

Resolution 0,0001 V

Accuracy  $\pm 0.5\%$

### Resistance

Measurement range up to 0 M  $\Omega$  ... 200  $\Omega$

Resolution 0,01 M  $\Omega$

Accuracy  $\pm 0.5\%$

### General technical data

Measuring functions HOLD

Connections Kelvin clamps

Display type TFT colour display

Display size 2,4 Inch

Storage medium Internal memory

Storage capacity 100 KB

Interface USB-C

Automatic power-off from...to 5 ... 30 min.

Automatic power-off can be deactivated Yes

Cable length 50 cm

Alarm optical, Acoustic

Calibration Manual

Test frequency 1 kHz

Menu language English, English (GB), Chinese

Protection class (device) IP42

Power supply 5 V / 1 A

Capacity 1000 mAh

Operating conditions -10 ... 45 °C, 0 ... 80 % RH

Storage conditions -20 ... 80 °C, 0 ... 80 % RH

Dimensions ( L x W x H ) 160 x 80 x 30 mm

Weight 222 g