

PCE Americas Inc.
711 Commerce Way
Suite 8
Jupiter
FL-33458
USA
From outside US: +1
Tel: (561) 320-9162
Fax: (561) 320-9176
info@pce-americas.com

PCE Instruments UK Ltd.
Units 12/13
Southpoint Business Park
Ensign way
Hampshire / Southampton
United Kingdom, SO31 4RF
From outside UK: +44
Tel: (0) 2380 98703 0
Fax: (0) 2380 98703 9
info@pce-instruments.com

www.pce-instruments.com/english www.pce-instruments.com

### **Technical Pallet Scale PCE-EP Serie**

# Pallet Scale PCE-EP 1500

Mobile Pallet Scale with 3 ranges, weight range up to 1.500 kg

This Pallet Scale PCE-EP 1500 allows you load directly in the ramp in no time at all. This model of Pallet Scale is the ideal solution for fast and precise mobile weighing in industrial and warehousing applications, in shipping and receiving applications and in inventory control. Now, you don't need to move with big efforts the pallet up to the scale. You only have to bring near the scale the merchandise to weigh, and you will be able to have a good control of the process. The Pallet Scale is transported without problems. In the front view you have a handle to elevate it and in the sides of the scale, you have some wheels. The display has been mounted in the back part of the Pallet Scale (ideal for its transport), nevertheless you can remove it and place it where you want.

- Three ranges for high accuracy
- Accuracy ±0,05 % of current value
- Large display 25 mm removable
- Automatic calculation of the tare, manual insert of tare, adder function
- Steel lacquering housing (it can be carried)
- Battery supply which allows an universal use
- Wheels and handle for a good transport
- Adjustable leveling foot
- Auto power off for battery protection












### **Dimensiones**



# **Technical Specifications**

Weight range 0 ... 1500 kg

Readability 500 g Reproducibility 500 g

Tare range in the full range

Response time <4 s

Display LCD 25 mm easy to read, high contrast with 4

keys

removable with 4 m cable lenght

Units kg
min. wheight 10 kg
máx. wheight 150 %

Calibration automatic (Through an external weight)

Operating temperature -10 ... +40 °C Housing metal (enameling)

Power supply 230 V / 50 Hz (via 12 V Net adaptor, included)

or 6 V internal rechargeable battery (included)

Protection IP 54
Weight 70 kg

# **Delivery contents**

1x Pallet Scale PCE-EP 1500, 1x display (3 m cable), 1x mains adapter 230 V - 12 V,1 x support and user's manual.