

Milliohmmeter PCE-MO 2001



Milliohmmeter PCE-MO 2001

(supplied with a water resistant brief-case, for measuring ranges from 100 $\mu\Omega$ to 2000 Ω)

This Milliohmmeter is supplied with a large $3\frac{1}{2}$ positions LCD display that shows the measurement values, which is veryeasy to read. With the Milliohmmeter you will be able to measureelectric resistance from $100 \mu\Omega$ to 2000Ω . To obtain measurement values, aconstant electric current is introduced inside an object to test thevoltage drop in it. Milliohmmeter has a housing protected against water splash and also it is delivered calibrated. If you wish, an ISO calibration certificate can be requested.

- ▶ It can be used to measure electric resistance in engine coils, generators, transformers, commutation circuits, for instance in parallel or adjoining commutation circuits, compressed commutation circuits or commutators and relays.
- ▶ To measure binding energy in mines, planes, boats and also for both industrial and home installations.
- ▶ Pitch control in cyclic systems (Ringbus) to be used in industry and home.
- ▶ To test and measure Read contacts.
- ▶ Compression elements control in over line current cables, for the control and maintenance of components such as connectors, contacts.
- ► Security: IEC-1010-1; CAT II 20 V

Specifications

Technical Specifications

 $0 \dots 200 \ m\Omega$ every $100 \ \mu\Omega/$

Ranges $0 \dots 2000 \text{ m}\Omega$: $1 \text{ m}\Omega/0 \dots 20 \Omega$: $10 \text{ m}\Omega/0 \dots 20 \Omega$

0 ... 200 Ω : 100 m Ω / 0 ... 2000 Ω : 1 Ω

 ± 0.75 % of the value +4 pos. (range up to 20 Ω)

 ± 0.75 % of the value +2 pos. (from 20 Ω)

Resolution 0.1/ 1/ 10 m Ω ; 0,1/ 1 Ω

1 mA (2000 Ω /200 Ω range)

Test current 10 mA (20 $\Omega/2$ Ω range)

100 mA (200 m Ω range)

Accuracy ±0.1 %

Measuring quota aprox. 0.4 s

Zero reset by hand: by means of a rotary wheel (± 50)

Overload indicator In case of overload a "1" appears

Power 230/110 VAC, 50/ 60 Hz Dimension of the tester 250 x 180 x 200 mm

cable length 50 cm (between the plug and the gripper)

Weight 680 g

Approval IEC-1010-1; CAT II

More information

More product info



Similar products

