



PCE Americas Inc.
711 Commerce Way
Suite 8
Jupiter
FL-33458
USA
From outside US: +1
Tel: (561) 320-9162
Fax: (561) 320-9176
info@pce-americas.com

PCE Instruments UK Ltd.
Units 12/13
Southpoint Business Park
Ensign way
Hampshire / Southampton
United Kingdom, SO31 4RF
From outside UK: +44
Tel: (0) 2380 98703 0
Fax: (0) 2380 98703 9
info@pce-instruments.com

www.pce-instruments.com/english
www.pce-instruments.com

Technical Surface Testing PCE-RT 10

**Surface texture meter / measurement range covers Ra and Rz /
LCD display with background lights / sensor made of a diamond / induction principle**

The surface texture meter PCE-RT 10 is a small, light device with simple navigation. Despite the fact that the device functions on a very complex and elaborate level, the measurement results can be gained easily and in a comfortable way. Due to its rugged design the device has a long lifetime. This device is calibrated on ISO, DIN, ABSI and JIS standards. The surface texture meter can be applied for various mechanical manufacturing processes as a controlling equipment. The device indicates all calculated measurement results on its LCD display any time. In order to measure the roughness of a surface, the sensor is to be placed onto that surface. Afterwards the sensor samples evenly the surface following its guide rail. Now the device will calculate the measuring values. Thus the indicated values are a result of the sensor's movement, while it is induced with electricity. The fast DSP processing supports quick measurements results, which are then shown on the surface texture meter's display.

- Ra and Rz measurement range
- Induction principle
- LCD display with background lights
- With threshold function
- Easy to transport
- Easy handling
- Diamond sensor
- Low fluctuation on display

Technical Specifications of the Surface Texture Meter

Measurement range

Ra	0.05 ... 10 µm / 1 ... 400 µinch
Rz	0.02 ... 100 µm / 0.78 ... 40 µinch

Measurement accuracy

General	±10 %
Fluctuation on display	Max. 6 %

Resolution

measurement range < 10 μ	0.001 μ
measurement range < 100 μ	0.01 μ
measurement range ≥ 100 μm	0.1 μ

Sensor

Measuring type	Induction principle
Radius of sensor	10 μm
Material of sensor	Diamond
Measuring force of sensor	16 mN (1.6gf)
Sensor angle	90 °
Vertical radius of probe head	48 mm

Measurement speed

Sampling length: 0.25	Vt = 0.135 mm/s
Sampling length: 0.8	Vt = 0.5 mm/s
Sampling length: 2.5	Vt = 1 mm/s
Returning	Vt = 1 mm/s

General Technical Specifications

Maximum hub	2.5 mm / 0.5 inch
Limit of frequency length	0.25 mm / 0.8 mm / 2.5 mm optical
Units	Rz, Ra
Display	4-digit LCD display, with background lights
Maximum surrounding temperature	0 ... +50 °C
Maximum surrounding air humidity	< 80%
Diameters	140 x 52 x 48 mm
Weight	280 g

Delivery Content of the Surface Texture Meter PCE-RT 10:

1 x Surface Texture Meter PCE-RT 10, 1x instruction manual