

Inspection Camera PCE-VE 200-S3



PCE-VE 200-S3 Inspection Camera

Extra small diameter (ø 3.7 mm) industrial endoscopic video inspection camera with 3 m / 9.8 ft longer length cable provides excellent image quality at an affordable price

PCE-VE 200-S is an industrial inspection camera, endoscope or borescope for the non-destructive evaluation (NDE) of engines, machines and more. This industrial borescope provides excellent image quality at an affordable price. An ideal tool for diagnosing issues in hard-to-reach places, the waterproof camera head features 6 LED lights with adjustable intensity for optimal illumination. In addition, digital image magnification or zoom of up to 4 times is available.

The borescope stores the recorded images and videos directly to a micro SD card memory. The 3 m / 9.8 ft cable length and **3.7 mm** / 0.14 in diameter allow the video inspection camera unique access to view the insides of walls, pipes, vents, ducts, engines and machinery, thus eliminating the need for costly and time-consuming dismantling. Mechanical engineering, manufacturing, automotive, aviation, construction, plumbing and heating, ventilation, air conditioning and refrigeration (HVACR) professionals alike find this video inspection camera useful in a variety of applications.

Not for medical use

- ▶ Waterproof camera head (IP67 protection class)
- ▶ 3.7 mm / 0.14 in diameter
- ▶ 3 m / 9.8 ft cable length
- ▶ 180° screen rotation
- ▶ 3.5" LCD display
- ▶ CMOS chip image sensor
- ▶ 1600 x 1200 pixels JPEG image / 640 x 480 pixels AVI video resolution
- ▶ Micro SD card memory
- ▶ Micro USB 2.0 and TV outputs

Customer review

"I received my PCE-VE 200-S3 borescope this past Thursday. To say I was quite pleased with it would be an understatement. I was unsure how good the resolution would be, but I needn't have worried: it was great! It was easy to use without even reading the instructions. It is one of the best values I have seen. I have already used it to find a small part that had fallen (twice) into the nether regions of my car while I was working on it. ... I will look to PCE in the future to fulfill similar needs."

- Tom Treue, McAlester, Oklahoma, USA

Subject to change

Specifications

Display	LCD, 3.5"
Resolution	1600 x 1200 pixels JPEG image / 640 x 480 pixels AVI video
Screen rotation	180°
Freeze functionality	Yes
Zoom	Up to 4 times digital image magnification
Menu languages	English, Spanish, French, German, Russian, Japanese, Simplified Chinese, Traditional Chinese
Cable diameter	3.7 mm / 0.14 in cable diameter
Cable length	3 m / 9.8 ft
Cable rigidity	Semi-flexible (semi-rigid spiral)
Image sensor	CMOS chip
Lighting	6 white LEDs (adjustable intensity)
Field of view / angle / perspective	90°
Sight depth	15 ... 100 mm / 0.59 ... 3.94 in
Storage medium	Micro SD card
Interfaces	Micro USB 2.0, TV output (PAL), Micro SD card slot
Power supply	Rechargeable 18650 Li-ion battery
Battery capacity	2600 mAh
Battery life	Up to 5 hours from full charge
Operating conditions	Main unit and probe, in air: -10 ... 50°C / 14 ... 122°F, rel. humidity 15 ... 90% Probe, in water: 5 ... 50°C / 41... 122°F
Fluid resistance	Main unit and probe: Machine oil, light oil or 5% saline
Protection against	Main unit: Blowing rain (battery compartment must be closed), not underwater Probe: Water, oil and dust, according to protection class IP67

More information

Manual



Datasheet



Video



Application Video



More product info



Similar products



Subject to change