

WATER ANALYSIS

PH METER

PCE-PH 228

pH Meter with GLP Data Management / High Accuracy ± 0.002 pH + 2 Digits

The advanced pH meter stands for precision, user-friendliness, and GLP compliance (Good Laboratory Practice). With a high-resolution LCD display, the pH meter provides a clear and concise presentation of measurement values. GLP compliance is ensured through automatic data recording and traceable documentation. It allows measurement of pH or redox value and temperature with external sensors.

A Permanent Measurement Verification (PMV) indicates to the operator, using a color bar, where the measurement value is located within the calibration range, providing insight into whether the measurement is in the correct range. User and sample management enable easy navigation and adjustment of measurement parameters on the pH meter.

ISO cal option

- » fast, precise pH and temperature measurement
- » redox measurement (with optional electrode)
- » GLP data management
- » easy 2, 3, 4, and 5-point calibration
- » calibration reminder
- » permanent Measurement Verification (PMV)
- » graphical display of measurement history
- » data logger



APPLICATION



TECHNICAL SPECIFICATIONS

pH	Measurement Range	-2 pH ... +20 pH	Optional accessories: Calibration Solution pH4 and pH7 and pH10 Order no.: PCE-PH4710 Electrode Storage Solution 3mol / l Order no.: PCE-SS0 pH Electrode IJ-44A Order no.: IJ-44A Diaphragm Cleaner with Thiourea Order no.: PCE-DCS-250 Cleaning solution pepsin / hydrochloric acid Order no.: PCE-GCS-500 REDOX-Electrode ORP-14 Order no.: ORP-14 Redox Solution +468 mV Order no.: PCE-RTS-468 Redox Solution +240 mV Order no.: PCE-RTS-220 Temperature sensor TP-07 Order no.: TP-07 pH-Electrode PE-03 Order no.: PE-03 Food pH-electrode Order no.: CPC-OSH-12-01
	Resolution	0.001 pH	
	Accuracy	± 0.002 pH + 2 digits	
	Electrode Designation	PE-03	
	Measurement Range	+1 pH ... +13 pH	
	Temperature Range	5 ... 60 °C	
	Application	Aqueous non-corrosive media	
	Reference Electrolyte	Ag/AgCl	
	Shaft Material	Epoxy resin	
	Shaft Length	160 mm	
	Shaft Diameter	12 mm	
	Cable Length	1 m	
	Redox		
	Measurement Range	-2000 mV ... +2000 mV	
	Resolution	1 mV	
	Accuracy	± 2 mV	
	Temperature Sensor		
	Minimum Temperature	-20 °C	
	Maximum Temperature	100 °C	
	Resolution	0.1 °C	
	Accuracy	± 0.5 °C (@ 20 °C)	
	General Technical Data		
	Storage Medium	Internal memory	
	Storage Interval from	1 s	
	Storage Interval to	12 h	
	Storage Capacity	32 GB	
	Storage Capacity		
	Additional Information	100 records with a maximum of 100,000 data points per record	
	Interface	USB-C	
	Menu Language	German, English, French, Spanish, Italian, Dutch, Portuguese, Turkish, Polish, Russian, Chinese, Danish, Japanese	
	Protection Class (Device)	IP52	
	Power Supply	5 V DC, 500 mA	
	Weight	252 g	
	Dimensions (L x W x H)	178 x 85 x 32 mm / 7 x 3,3 x 1,2 in	
	Operating Conditions	-20 ... 65 °C, 10 ... 95 % r.H	
	Storage Conditions	-20 ... 65 °C, 10 ... 95 % r.H	
	Languages of the Manual	German, English	
	Batteries and Accumulators		
	Type	Lithium polymer battery	
	Lithium Info	Lithium in the product (built-in or included)	
	Capacity	2500 mAh	
	Voltage	3.7 V	
	System	Secondary: Rechargeable battery	
	Quantity	1	



Subject to change without notice