

MATERIAL THICKNESS MEASUREMENT

WALL THICKNESS GAUGE PCE-TG 300 SERIES WITH BLUETOOTH

With a wide measuring range of up to 600 mm

The PCE-TG 300 is a wall thickness gauge with special probes for various applications. In general, the wall thicknesses of all homogeneous materials can be measured with the PCE-TG 300. For damping or scattering materials such as plastic or cast iron, a special probe is available. An angled 90 ° probe also enables measurements at hard-to-reach measuring positions. The speed

of sound can be set freely and thus adapted to a wide variety of materials. The measured values are displayed directly on the easy-to-read TFT colour display.

ISO cal option

- ▶ wide measuring range
- ▶ various probes available
- ▶ battery operation
- ▶ fault and cavity detection
- ▶ internal measurement data memory
- ▶ printing via Bluetooth



APPLICATION



TECHNICAL SPECIFICATIONS

Measuring range	PE: pulse-echo mode 0.65 ... 600 mm (steel)	PCE-TG 300-NO5	
Accuracy	±0.04 mm H [mm] (< 10 mm); ±0.4 % H [mm] (> 10 mm)	Frequency / Ø	5 MHz / 10 mm
	H refers to the material thickness of the	Measurement range	1 ... 600 mm (steel)
workpiece		Minimum pipe diameter	20 x 3 mm
Resolution	0.1 mm / 0.01 mm / 0.001 mm (adjustable)	Description	normal measurement
Measurable materials	Metals Plastics Ceramics Epoxy resin Glass and all homogeneous materials	PCE-TG-300-NO5/90 NO5 / 90 °	
		Frequency / Ø	5 MHz / 10 mm
Working modes	Pulse echo mode (fault and cavity detection) Echo-Echo mode (hiding layer thicknesses, e.g. lacquers)	Measurement range	1 ... 600 mm (steel)
Calibration	Sound velocity calibration Zero point calibration Two-point calibration	Minimum pipe diameter	20 x 3 mm
View mode	Normal mode, scan mode, difference mode	Description	normal measurement
Units	mm / inch	PCE-TG 300-NO7	
Data transfer	Printing via Bluetooth / USB 2.0	Frequency / Ø	7 MHz / 6 mm
Memory	Non-volatile memory with 100 data groups with 100 data sets each	Measurement range	0.65 ... 200 mm (steel)
Operating time	Continuous operation 100 h Automatic stand-by mode (adjustable) Automatic power off mode (adjustable)	Minimum pipe diameter	15 x 2 mm
Power supply	4 x AA battery 1.5 V	Description	for thin-walled or strongly curved pipes
Display	320 x 240 pixel TFT LCD colour display with brightness adjustment	PCE-TG 300-HT5	
Operating conditions	0 ... 50 °C / 32 ... 122 °F, ≤80 % RH non condensing	Frequency / Ø	5 MHz / 12 mm
Storage conditions	-20 ... 70 °C / -4 ... 158 °F, ≤80 % RH non-condensing	Measurement range	1 ... 600 mm (steel)
Dimensions	185 x 97 x 40 mm / 7.3 x 3.8 x 1.6 in	Minimum pipe diameter	30 mm
Weight	375 g / < 1 lb	Description	for high temperatures (max. 300 °C)
Models			
PCE-TG 300-P5EE			
Frequency	5 MHz		
Diameter	10 mm		
Measurement range	P-E: 2 ... 600 mm, E-E: 2,5 ... 100 mm		
diameter	20 x 3 mm		
Description	normal measurement and E-E test		
PCE-TG 300-NO2			
Frequency / Ø	(not suitable for curved materials) 2.5 MHz / 14 mm		
Measurement range	3 ... 40 mm (steel) 3 ... 300 mm (steel)		
Description	For damping / scattering materials (plastics, cast iron)		



Subject to change without notice