

THICKNESS METER PCE-TG 75

Material thickness measurement up to 225 mm

The thickness meter can measure material thicknesses up to 225 mm / 8.85". So that the material thickness of a wide variety of homogeneous materials can be measured, it is possible to store the corresponding speed of sound in the thickness meter. For materials such as steel, aluminum, zinc, silver and gold, the appropriate sound speeds are already stored in the

device library. This means that the thickness meter can be used universally. With the limit value function in the thickness meter, individual maximum and minimum values can be stored. If the measured value of the test piece is outside the limits, the thickness meter signals this visually.

ISO cal option

- measured value memory
- calibration reference on the housing
- automatic shutdown
- material thickness measurement up to 225 mm / 8.85"
- battery status indicator
- optionally with ISO calibration certificate



APPLICATION



50



TECHNICAL SPECIFICATIONS

Measuring range Resolution

1.00 ... 225.0 mm / 0.04 ... 8.85" 0.01 mm at ≤99.99 mm

0.1 mm at ≥100.0 mm

±0.5 % of measured value + 0.05 mm

Storage space 500 measured values

Probe frequency 5 MHz

Standard sensor sensor PCE-TG 5M10d

Further specifications Adjustable speed of sound 1000 ... 9999 m/s Smallest pipe diameter Material library

Calibration reference

Display

Accuracy

Power supply Automatic switch-off Ambient conditions

non-condensing Dimensions Weight

Ø20 x 3 mm (steel) 15 memory locations

2.4 inch TFT LCD color display with brightness adjustment 3 x 1.5 V AA batteries

switched off, 2, 5, 10, 30 minutes 0 ... 40 °C / 32 ... 104 °F, <90 % RH,

163 x 82 x 38 mm / 6.4 x 3.2 x 1.5" 320 g / 11.2 oz

Optional accessories:

Standard probe for the PCE-TG 75/150

Order no.: PCE-TG 5M10d



Subject to change without notice