

Material Surface Roughness Tester PCE-RT 10-ICA Incl. ISO Calibration Cert.



PCE-RT 10-ICA Material Surface Roughness Tester Incl. ISO calibration Certificate

Measurement range covers Ra and Rz /

LCD display with background light / Sensor made of a diamond / Induction principle

The Material Surface Roughness Tester PCE-RT 10-ICA is a small, lightweight device with simple navigation. Despite the fact that the device functions on a very complex and elaborate level, the measurement results can be gained quickly and easily. Due to its rugged design the device has a long lifetime. This device is calibrated on ISO, DIN, ABSI and JIS standards. The surface texture meter can be applied for various mechanical manufacturing processes as a controlling equipment. The device indicates all calculated measurement results on its LCD display any time. In order to measure the roughness of a surface, the sensor is to be placed onto that surface. Afterwards the sensor samples evenly the surface following its guide rail. Now the device will calculate the measuring values. Thus the indicated values are a result of the sensor's movement, while it is induced with electricity. The fast DSP processing supports quick measurements results, which are then shown on the surface texture meter's display.

Calibration certificates are issued specifically for the customer and are excluded from the right of return.

- ▶ Ra and Rz measurement range
 - ▶ Induction principle
 - ▶ LCD display with background lights
 - ▶ With threshold function
 - ▶ Easy to transport
 - ▶ Easy handling
 - ▶ Diamond sensor
 - ▶ Low fluctuation on display
- Incl. ISO calibration certificate**

Specifications

Standards	GB/T6062, ISO4287, DIN4768, JIS B, ANSI46.1
Display	LCD
Parameters	Ra, Rz
Range	Ra: 0.05~10.00 µm Rz: 0.1~50.0 µm
Accuracy	±15 %
Fluctuation of Display Value	10 %
Resolution	0,001 / 0,01 / 0,1

Sensor

Radius of Probe Pin	10 µm
Material of Probe Pin	Diamond
Measurement Force of Probe	16 mN(1.6gf)
Probe Angle	90°
Vertical Radius of Guiding Head	48 mm
Maximum Driving Stroke	12,5 mm / 0,5 inch
Cutoff length(l)	0,25 mm, 0,8 mm, 2,5 mm

Driving Speed

Sampling	when Length = 0,25 mm, Vt = 0,135 mm/s
Sampling	when Length = 0,8 mm, Vt = 0,5 mm/s
Sampling	when Length = 2,5 mm, Vt = 1 mm/s
Returning	Vt = 1 mm/s

Evaluation Length	1~2L Optional
Operating Conditions	Temp: 0 ~ 50 °C Humidity: <80 % RH
Power Supply	4 x 1.5 VAA (UM-3) Battery
Dimensions	128 x 80 x 30mm
Weight	280 g

More information

Manual



Video



More product info



Similar products



Subject to change