

CO2 Analyzer PCE-CMM 10







CO2 analyzer PCE-CMM 10

CO2 meter / Battery operation / Alarm limits / 400 ... 5000 ppm / Temperature measurement / Visual and acoustic alarm / Automatic switch-off / USB charging / Units can be changed / LC display / Temperature range -10 ... 50°C (4 ... 122°F)

The CO2 measuring device PCE-CMM 10 is a multi-function measuring device for measuring the air quality. This CO2 meter measures synchronously the CO2 concentration, the air temperature and the humidity. In addition, the CO2 meter has permanently programmed alarm limits. As soon as the currently measured CO2 measured value exceeds the alarm limit, the alarm is activated. The user is alerted to the CO2 meter by an audible and visual signal.

Using the built-in USB interface, you can continuously charge the CO2 meter to your PC workstation, for example. Thanks to the small blue shape, you can optimally position the CO2 meter at your workplace. Due to the 3 inch display and the strong backlight, you can read the measured values optimally.

- ► CO2 measurement
- ▶ Battery operation
- Limit exceeded
- ► Backlight
- ► Air temperature
- ► Table housing
- ▶ Humidity
- Beep

Specifications

Measuring range CO2 400 ... 5000 ppm

Resolution 1 ppm

Accuracy \pm (5% + 50 ppm) between 400 ... 2000 ppm

and an atmospheric pressure of 1

Measuring range temperature -10.0 ... 50.0°C / 14 ... 122°F

Resolution $0.1^{\circ}\text{C} / 0.18^{\circ}\text{F}$ Accuracy $\pm 1^{\circ}\text{C} / 1.8^{\circ}\text{F}$

(can be influenced by its own waste heat)

Measuring range humidity 0 ... 99% rh
Resolution 1% rh

Accuracy \pm (5% at 25°C / 77°F) between 10 ... 90% rh

Sensor NDIR principle

ABC Automatic baseline correction

Audio alarm Buzzer

Visual alarm Red backlight

Display 3 inch LC display

battery indicator Four-level display

display frequency 3 seconds

Automatic shutdown turns itself off after 2 hours

Backlight White backlight

Working conditions $0 \dots 50^{\circ}\text{C} / 32 \dots 122^{\circ}\text{F}, 0 \dots 85\% \text{ rh}$ Storage conditions $-20 \dots 60^{\circ}\text{C} / -4 \dots 140^{\circ}\text{F}, 0 \dots 95\% \text{ rh}$

Power supply Built-in 3.7V DC battery

Weight 195 g / < 1 lb

Dimensions 75 x 55 x 130 mm / 3 x 2.2 x 5.1 in

More information

Manual

More product info



Similar products

