

Infrared Thermometer PCE-893



Infrared Thermometer PCE-893

Laser temperature meter for easy measurement of surface temperatures /

Fast response time / Adjustable emissivity / Max-Min function / Alarmfunction / Measuring range up to 1200 °C / 2192 °F /

Thermocouples type K connectable/ Software for PC connection

The infrared thermometer PCE-893 is suitable for simple temperature measurements. The emissivity of the surface can be adjusted on the PCE-893 thermometer. Thus, the thermometer PCE-893 is suitable for almost all surfaces. The dual laser of the thermometer PCE-893 marks the exact center of the measurement spot. This helps the user considerably with non-contact temperature measurement. The thermometer PCE-893 has a backlit display. In addition to the emissivity setting, the user can set limit value alarms over the entire measuring range of the PCE-893 thermometer. The measuring range is from -50 °C to + 1200 °C / -58 ... 2192 °F. The measuring spot ratio of the thermometer PCE-893 is 50:1.

In addition to the infrared measurement, a variety of thermocouples Type-K can be connected to the thermometer. Here measurements up to 1370 °C / 2498 °F are possible. The included software and the USB port on the thermometer allow the operator to analyze and store all measurement data on the PC both graphically and in a table.

- ▶ Dual laser shows the spot center
- ▶ Adjustable emissivity
- ▶ Illuminated LCD
- ▶ Measured value transmission to a PC
- ▶ Non-contact temperature measurement
- ▶ Measurement spot ratio 50: 1 infrared optics
- ▶ Temperature measurement up to 1200 °C / 2192 °F
- ▶ Thermocouple type-K can be connected

Typical applications of the infrared thermometer PCE-893

- ▶ Food monitoring
- ▶ Hygiene tests
- ▶ Road construction
- ▶ Control cabinet monitoring
- ▶ Heating and air conditioning technology
- ▶ Production monitoring
- ▶ Temperature measurement on motors
- ▶ Electronic components
- ▶ Fuse box

*****ATTENTION*** Our temperature sensors are designed for industrial and laboratory surface temperature measurement ONLY. They are not designed or certified for body temperature measurement or for medical use.**

Subject to change

Specifications

Infrared measurement

Infrared measurement	-50 ... 1200 °C / -58 ... 2192 °F
Resolution	0.1 at display <1000 1 at display >1000
Accuracy	±3 °C / 5.4 °F (-50 ... 20 °C / -58 ... 68 °F) ±1 % ±1 °C / ±1.8°F (20 ... 500 °C / 68 ... 932°F) ±1.5 % (500 ... 1000 °C / 932 ... 1832 °F) ±2 % (1000 ... 1600 °C / 1832 ... 2912 °F)

The accuracies apply at an ambient temperature of 23 ... 25 °C (73 ... 77 °F)

Repeatability	±1.5 °C / 2.7 °F (-50 ... 20 °C / -58 ... 68 °F) ±0.5 % or ±0.5 °C / 0.9 °F (20 ... 1000 °C / 68 ... 1832 °F) ±1.0 % (1000 ... 1600 °C / 1832 ... 2912 °F)
---------------	---

Thermoelement

Measuring range	-50 ... 1370 °C / -58 ... 2498 °F
Resolution	0.1 at display <1000 1 at display >1000
Accuracy	±2.5 °C / ±3.6°F (-50 ... 0 °C / -58 ... 32°F) ±0.5 % ±1.5 °C / 3 °F (0 ... 1370 °C / 32 ... 2498 °F)

Measurement spot ratio	50:1
Response time	150 ms
Spectral range	8 ... 14 µm
Emissivity	Adjustable 0.10 ... 1.0
Display overrange	The display will show "-----"
Display laser diode	LCD with backlight
Output	<1 mW
Wavelength	630 ... 670 nm
Classification	Class 2
Power supply	9 V block battery
Operating conditions	0 ... +50 °C / 32 ... 122 °F
Storage conditions	-10 ... +60 °C / 14 ... 140 °F
Weight	ca. 282 g without battery
Dimensions	200 x 55 x 150 mm / 7.8 x 2.1 x 5.9"

More information

Manual



More product info



Similar products



Subject to change